

Physical Data

| Length | Width | Height | Weight | |
|------------|-----------|---------------|--------|-----------|
| 276 inches | 98 inches | 111.75 inches | 12250 | pounds |
| 701 cm | 249 cm | 284 cm | 5557 | kilograms |

Working position = 353" long / 165" high / Tongue 2,850 lbs

Engine Specifications

| | | | |
|-------|--------|---------------------|-----------|
| Mfg. | Kohler | Model | CH205 |
| Fuel | Gas | Engine Oil | SAE 10W30 |
| Volts | NA | Rated Engine RPM | 3600 |
| Phase | NA | Rated Engine Output | 20 HP |
| HZ | NA | | 14.71 kW |

Production Capability Data

| | |
|---------------------------------------|-----------------------|
| Tire size range for bale production | Min = 13" car tire |
| | Max = half truck tire |
| Compaction Cycle Time | 30 seconds |
| Average Weight of Tire Bale | 2000 pounds/plus |
| | 907 kilograms |
| Average Hourly Production | 3 - 4 Tire Bales |
| Avg Hrly Production based on Tire Wgt | 8000 pounds |
| | 3628 kilograms |

Design and specifications are subject to change without notice

Hydraulic System Operating Parameters

| | | | |
|--|------------|-----------------------------|---------------------------------|
| Hydraulic Oil Tank Capacity | 70 gallons | Hydraulic Oil Specification | Dexron III High Temperature ATF |
| | 265 litres | | |
| Hydraulic System Operating Pressure (Pressure @ Punch Cylinder) | 1900 PSI | | |
| | 13,100 kPa | | |

Standard Product Features

| | | | |
|--------------------------|----------------------------|---------------------|--|
| Manual tire loading | Manual Door Locks | E-Stop | Safety Hydraulic Override Limit Switch |
| 6.5 gallon fuel tank | Oil & Temp Warning Lights | Operator Platform | 5 Wire Bale Chamber |
| HD Platen Assembly | 6X54 Compression Cylinder | Bale Ejector Chains | |
| 70 Gallon Hydraulic Tank | HD Steel Hold-Down Fingers | | |

Recommended Spare Parts List

| Description | Qty | Part # | Description | Qty | Part # |
|------------------|-----|--------|----------------------------|-----|--------|
| Hydraulic Filter | 2 | 6804 | Pre-Clean Air Filter - Gas | 2 | 6621 |
| Hold Down Finger | 5 | 6099 | Oil Filter - Gas | 2 | 6622 |
| Hold Down Spring | 10 | 6100 | Fuel Filter - Gas | 2 | 6623 |
| Air Filter - Gas | 2 | 6620 | Replacement Key - Gas | 1 | 6813 |
| | | | | | |

REUSE

REDUCE

RECYCLE

